


100-F20R-WZ: Henco-Floor PE-Xc/AL/PE-Xc Ø20X2 100M



Commercial information

Henco multilayer pipes offer all the **advantages** of metal and plastic:

- Aluminium inner core, seamlessly welded longitudinally
- 100 % oxygen-tight
- Minimal linear expansion coefficient comparable to metal
- Fully corrosion-resistant, including against chemical and electrochemical impacts
- Dampens noise, as typical of a plastic pipe
- Inner and outer pipe made of electron-beam cross-linked polyethylene
- High resistance to pressure and temperature
- Smooth surface: low pressure loss
- As light as a plastic pipe
- Flexible, easy to bend. The pipe retains its curved shape even in low temperatures

Basic unit dimensions

Height	20 mm
Length	1,000 mm
Width	20 mm
Net weight	0.147 kg

Certificates

Applications

Underfloor Heating

Solutions

Building installations, Industry, Underfloor heating, Utility

Technical characteristics

Material intermediate layer	Aluminium	Outer pipe diameter	20 Millimetre
Material outer layer	Plastic (expired)	Medium temperature (continuous)	- Degrees celsius 10 6 0
Glass-fibre reinforced	✘	Max. medium temperature (momentarily)	60 Degrees celsius
Diffusion-proof	✓	Max. operating pressure at 20 °C	6 Bar
Nominal diameter	DN 16	Max. operating pressure at max. medium temperature	6 Bar
System specific	✓	Wall roughness	0.00 Millimetre 7
Flexible	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Suitable for surface mounting	✘	Min. bending radius	60 Millimetre
Pipe colour	White	Min. bending radius without tools	60 Millimetre
With mantle pipe	✘	Thickness of thermal insulation	0 Millimetre
With heating cable	✘	Lambda value	0.43 Watt per metre Kelvin
With thermal insulation	✘	Outer diameter thermal insulation	0 Millimetre
Capped	✘	Outer width rectangular insulation	0 Millimetre
UV resistant	✘	Outer height rectangular insulation	0 Millimetre
Halogen free	✓	Water content	0.20 Litre per metre 1
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		