

Walraven BISOFIX® E19 + HD500

(D0320)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	D	G	W x H x L	Is	Fa,z
Unit description	mm		mm x mm x mm	mm	N
I193304076	76.1	M10/M12	193 x 170 x 50	25.3	575
I193304089	88.9	M10/M12	200 x 177 x 50	25.3	875
I193304102	101.6	M10/M12	215 x 191 x 50	25.3	1,000
I193304108	108	M10/M12	240 x 207 x 50	25.3	1,075
I193304114	114.3	M10/M12	240 x 207 x 50	25.3	1,250
I193304133	133	M10/M12	274 x 240 x 100	26.2	1,475
I193304140	139.7	M10/M12	274 x 240 x 100	25.3	1,700
I193304160	159 - 160	M10/M12	290 x 256 x 100	25.3	1,950
I193304168	168.3	M10/M12	290 x 256 x 100	25.3	2,125
I193304219	219.1	M16	360 x 315 x 100	25.3	3,525
I193304273	273.1	M16	403 x 358 x 100	25.3	3,525