

Walraven BISOFIX® E19 + Bifix® G2

(D0318)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	D	G	W x H x L	Is	Fa,z
Unit description	mm		mm x mm x mm	mm	N
I193008010	10	M8/M10	266 x 280 x 400	19.3	100
I193008012	12	M8/M10	91 x 73 x 50	19.3	100
I193008015	15	M8/M10	97 x 79 x 50	19.5	100
I193008018	17.2 - 18	M8/M10	97 x 79 x 50	19.3	100
I193008022	21.3 - 22	M8/M10	104 x 86 x 50	19.3	100
I193008028	26.9 - 28	M8/M10	110 x 92 x 50	19.3	100
I193008035	33.7 - 35	M8/M10	118 x 100 x 50	19.3	100
I193008042	42.4	M8/M10	125 x 107 x 50	19.3	150
I193008048	48.3	M8/M10	134 x 115 x 50	19.3	225
I193008054	54	M8/M10	148 x 129 x 50	23	225
I193008057	57	M8/M10	148 x 129 x 50	23	225
I193008060	60.3	M8/M10	148 x 129 x 50	19.9	350
I193008064	64	M8/M10	155 x 137 x 50	25.3	350
I193008070	70	M8/M10	172 x 154 x 50	27.3	452
I193008076	76.1	M8/M10	172 x 154 x 50	25.3	575
I193008089	88.9	M8/M10	181 x 162 x 50	25.3	875
I193008102	101.6	M8/M10	201 x 183 x 50	25.3	1,000
I193008108	108	M8/M10	201 x 183 x 50	25.3	1,075
I193008114	114.3	M8/M10	217 x 195 x 50	25.3	1,250
I193008133	133	M8/M10	248 x 227 x 100	26.2	1,475
I193008140	139.7	M8/M10	248 x 227 x 100	25.3	1,700
I193008160	159 - 160	M8/M10	261 x 239 x 100	25.3	1,950
I193008168	168.3	M8/M10	275 x 253 x 100	25.3	2,125