

ATTESTATION OF CONFORMITY

Issued to: EcoFlow Inc.
RM 401, Plant #1, Runheng Industrial Zone, Fuyuan Road, Zhancheng Community,
Fuhai Street, Bao'an District, Shenzhen City, Guangdong, China

For the product: DBO (EcoFlow STREAM Gateway)

Trade name:



Type/Model: EF-ST-GW-EU-1, EF-ST-GW-UK-1

Ratings: See annex

Manufactured by: EcoFlow Inc.
RM 401, Plant #1, Runheng Industrial Zone, Fuyuan Road, Zhancheng Community,
Fuhai Street, Bao'an District, Shenzhen City, Guangdong, China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 61439-1:2021
EN IEC 61439-3:2024

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no 4957788.50.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 14 July 2026

Number: 4957788.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou Branch

Phoebe Chen
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Annex

Document no. : 4957788.01AOC

Ratings:

Items	Parameters
Rated voltage (U_n)	230/400V AC
Rated current of the assembly (I_nA)	32A (Smart port/ grid terminal input) 13A (Socket input for EF-ST-GW-UK-1) 16A (Socket input for EF-ST-GW-EU-1)
Rated current of a main outgoing circuit (I_{nc})	32A (Smart port/ grid terminal output) 13A (Socket output for EF-ST-GW-UK-1) 16A (Socket output for EF-ST-GW-EU-1)
Group rated current of a main circuit (I_{ng})	Same as I_nA
Rated short-time withstand current (I_{cw})	6kA
Rated conditional short-circuit current of an assembly (I_{cc})	6kA
Rated impulse withstand voltage (U_{imp})	4kV
Overvoltage category.....	III
Pollution degree	3
Types of system earthing	TN system
Degree of protection	IP54
Mechanical impact protection.....	IK10
Indoor and/or outdoor installation.....	Indoor

End