

# Concord

## BEACON XXL MB HO 4K L3 WHT 2059314



### Features

- 2059314 BEACON XXL MB HO 4K L3 WHT Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for double height spaces, retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 50° medium beam, optics: Silicone lens for controlled beam, colour temperature: 4000K neutral white, total system power: 48W, total fixture output: 4884lm, luminaire efficacy: 102lm/W, LOR: 100%, colour rendering: Ra 85 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1200mA, electronic driver, non-dimmable, switched only, power factor: 0.98 electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, lockable positioning using Allen key, ...

### Product Overview


Product name	BEACON XXL MB HO 4K L3 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
E-number FI	4278871
E-number SE	7401088
Fixture luminous flux (lm)	4884
Luminaire efficacy (lm/W)	101.75
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White

# Concord


## BEACON XXL MB HO 4K L3 WHT 2059314

CRI (Ra)	85
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP20
Product EAN number	5025768593149
Warranty	5 years

### Photometry



### Technical drawings



# Concord

BEACON XXL MB HO 4K L3 WHT  
2059314

## Data table

### GENERAL DATA

Product name	BEACON XXL MB HO 4K L3 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
Performance ambient temperature Tq (°C)	25
E-number FI	4278871
E-number SE	7401088
Warranty	5 years

### OPTICAL DATA

Fixture luminous flux (lm)	4884
Luminaire efficacy (lm/W)	101.75
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Photobiological Risk Group	RG1

### ELECTRICAL DATA

Total power consumption (W)	48
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast

# Concord

## BEACON XXL MB HO 4K L3 WHT 2059314

Drive current (mA)	1200
--------------------	------

Energy Efficiency Class (A->G) of contained light source	D
--	---

### LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

Lifespan L80 B20	100000
------------------	--------

Lifespan L90 B10	55500
------------------	-------

### PHYSICAL DATA

Housing colour	White
----------------	-------

IP rating	IP20
-----------	------

Diffuser finish	Diffuse
-----------------	---------

Nominal Product Length (mm)	85
-----------------------------	----

Nominal Product Width (mm)	168
----------------------------	-----

Weight (kg)	1.375
-------------	-------

### PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5025768593149
--------------------	---------------

Packaging single width (cm)	19.5
-----------------------------	------

Packaging single depth (cm)	20.0
-----------------------------	------

DUN14 (outer)	05025768593149
---------------	----------------

Packaging outer length / height (cm)	25.0
--------------------------------------	------

### SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----