

BAP-FFV32Z06: Inox ball valve with handle, press x swivel nut Ø32 x 1"



Commercial information

With the BAP-FFV valve assortment, Henco offers stainless steel valves that guarantee an extra-long life, regardless of water hardness. They are also the right solution for "heavy duty" environments such as hospitals, farms, car washes, laboratories, etc. Also suitable for osmosis and demineralised water.

This stainless steel valve offers the user a unique range of benefits:

- · Connections: press x swivel
- KIWA and DVGW certified
- Available in diameters from 16 to 32 mm
- With removable levers
- · Equipped with Leak Before Press functionality
- · With color indication for water type

_			
Ce	rt 11	rica	ıtes

KIWA SE, KIWA

Applications

Potable water, Heating, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility



Technical characteristics

reciffical characterist	103	
Housing material	Stainless steel	Medium temperature (continuous)
Material quality	Stainless steel 316 L (1.4404)	Length of connection 1
Surface protection housing	None	Working length connection 1
Material ball	Stainless steel	Length of connection 2
Surface protection ball	None	Working length connection 2
Material spindle	Stainless steel	Handgrip length
Material primary spindle seal	Other	
Material secondary spindle seal	Other	
Nominal diameter connection 1	1 inch (25)	
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)	
With coupling connection 1	×	
Nominal diameter connection 2	DN 20	
Connection 2	Press sleeve	
With coupling connection 2	×	
Contour code connection 2	TH/BE	
Article compression class	PN 16	
With drain valve	×	
With drain possibility (connection)	×	
With filter	×	
With thermometer	×	
Model	Straight	
With insulation shell	×	
FM quality mark	×	
UL quality mark	×	
ULC quality mark	×	
LPCB quality mark	×	
Fire-safe	×	
Medically clean	×	
Grease-free	×	
Operation	Lever handle	
Full bore	✓	
VdS quality mark	×	
DVGW quality mark for gas	×	
DVGW quality mark for water	×	
KIWA certified	✓	
Type approval according to BBR/EKS	×	

Related products

Product codeGTINDescriptionBE3205414764437845Henco Jaws (universal) BE-Profile 32x3

PRESSCHECK1432 05414764437845 Henco Tool to control the accuracy of a pressing Ø14-32

Image

-35|135 Degrees celsius

66 Millimetre

56.4 Millimetre

78.5 Millimetre 36.5 Millimetre

12.2 Millimetre





