

Product data sheet

Item No. 96.442.2004.1

Cable assembly RST20I4KS-S 15P 20SW

Connection cable, male - free end, length 2m, RST20i4, 4 pole, 250/400V, 16A, cable type H05VV, cross section 1,5mm², color of coding: black



Item No.	96.442.2004.1
EAN	4015573912083
Order Unit	25 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

Kabeltype/cable type H05VV-F4G1,5

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.442.XX04.1	XX in dm-Schritten	96.442.1004.1 = 10dm/L= 1000mm	RST2014KS-S 15P 10SN
96.442.XX04.0		96.442.1004.0	RST2014KS-S 15P 10GL
U6.442.XX04.1	XX in m-Schritten	U6.442.1204.1 = 12 m/L=12000mm	RST2014KS-S 15P X12SN
U6.442.XX04.0		U6.442.1204.0	RST2014KS-S 15P X12GL

Farbe/color	
schwarz/black	.1
lichtgrau/light grey	.0

2006	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
11.05.			T 96.442.1004.0 01K	a

KONTEKT LEITUNG
 ready made cable
 Schraubenschluss ohne Drahtschutz/ screw-connection without wire protection
 Kodierung/Keying 0 (250V/20A)