

Concord

Raiden IP66 30KLM 830 Symmetric Wide 2824016



Features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 3000K, Non-dimming, 29300lm, 221W, 133lm/W, CRI80, Symmetric Wide beam angle 60°, 100000 hrs L90B50 lifespan, 561x569x76mm (LxWxH) dimensions, 12.5kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.


Product Overview

Product name	Raiden IP66 30KLM 830 Symmetric Wide
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Fixture luminous flux (lm)	29300
Luminaire efficacy (lm/W)	133
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	221
Electrical protection	Class I
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240166
Warranty	5 years

Concord

Raiden IP66 30KLM 830 Symmetric Wide
2824016

Photometry



Technical drawings

