


## BAP-H2020: Ball valve with handle Press 20x20



### Commercial information

Messing bolkraan met 2 perskoppelingen. Handvat heeft een rode coating

#### Certificates

#### Applications

Potable water, Heating, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Surface protection ball	None	Diameter bolt hole	20
Material secondary spindle seal	Ethylene-propylene diene monomer rubber (EPDM)	Outer pipe diameter connection 1	20 Millimetre
Nominal diameter connection 1	DN 10	Outer pipe diameter connection 2	20 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
With coupling connection 1	✓	Wrench width	0 Millimetre
Contour code connection 1	TH/BE	Wrench width union nut	0 Millimetre
Nominal diameter connection 2	DN 10		
Connection 2	Press sleeve		
With coupling connection 2	✓		
Contour code connection 2	TH/BE		
Sealing	Polytetrafluoroethylene (PTFE)		
With drain valve	✗		
With drain possibility (connection)	✗		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Operation	Lever handle		
Full bore	✗		
KIWA certified	✗		

## Related products

Product code	GTIN	Description
BE20	05414764059375	Henco Jaws (universal) BE/TH-Profile 20x2
100-R200216	05414764059375	Henco RIXc Ø20x2 100m

### Image

