

Beacon LED XXL - High Output

BEACON XXL WB HO 3K L3 BLK
2059315




PRODUCT OVERVIEW

| | |
|-----------------------------|----------------------------|
| Product name | BEACON XXL WB HO 3K L3 BLK |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Track mounting |
| Environment | Internal |
| E-number FI | 4278861 |
| E-number SE | 7401271 |
| Warranty | 5 years |
| Fixture luminous flux (lm) | 5118 |
| Luminaire efficacy (lm/W) | 106.62 |
| LOR (%) | 100 |
| Colour temperature (K) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 85 |
| Colour Consistency (SDCM) | 3 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 48 |
| Electrical protection | Class I |
| Control gear type | Electronic ballast |
| Housing colour | Black |
| IP rating | IP20 |
| Product EAN number | 5025768593156 |

PHOTOMETRY

Beacon LED XXL - High Output BEACON XXL WB HO 3K L3 BLK 2059315



| Distance [m] | Cone diameter [m] | Beam angle [°] | Beam angle [°] | Illuminance [lx] |
|--------------|-------------------|----------------|----------------|------------------|
| 0.5 | 0.66 | 50° | 33.8° | 1876 |
| 1.0 | 1.32 | 50° | 33.8° | 469 |
| 1.5 | 1.99 | 50° | 33.8° | 209 |
| 2.0 | 2.66 | 50° | 33.8° | 119 |
| 2.5 | 3.31 | 50° | 33.8° | 72 |
| 3.0 | 3.97 | 50° | 33.8° | 52 |

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 67.0°)

TECHNICAL DRAWINGS

