





Color: ■ gray



Dimensions in mm

- Sockets with IDC for tapping individual conductors without stripping
- Three-pole sockets automatically cut "live" conductors (e.g., door switches in elevator shafts)
- Sockets available with additional mounting flanges

Electrical data

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	500 V	630 V	1000 V
Rated surge voltage	6 kV	6 kV	6 kV
Rated current	10 A	10 A	10 A

Approvals per	UL 1059		
Use group	B	C	D
Rated voltage	-	600 V	-
Rated current	-	10 A	-

Approvals per	CSA		
Use group	B	C	D
Rated voltage	-	600 V	-
Rated current	-	10 A	-

Connection data

Total number of potentials	6
Number of connection types	1
Number of levels	1

Connection 1	
Connection technology	IDC connection
Fine-stranded conductor	0.75 ... 1.5 mm² / 18 ... 16 AWG
Pole number	6

Physical data

Width	43 mm / 1.693 inches
Height	16 mm
Depth	30 mm / 1.181 inches



Mechanical data	
Variable coding	No
Mounting type	Mounting flange
Plug-in connection	
Contact type (pluggable connector)	Female connector/socket
Connector (connection type)	for conductor
Mismating protection	No
Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Brass
Contact plating	Tin
Fire load	0.31 MJ
Weight	11.9 g
Environmental requirements	
Limit temperature range	-60 ... +85 °C
Commercial data	
Product Group	13 (Misc. Multi Conn. System)
eCl@ss 10.0	27-14-11-06
eCl@ss 9.0	27-14-11-06
ETIM 8.0	EC001284
ETIM 7.0	EC001284
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918253468
Customs tariff number	85366990990
Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption



Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 60998	2174149.01A
CSA DEKRA Certification B.V.	C22.2 No. 158	LR 18677-43
UL UL International Germany GmbH	UL 1059	E45172

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 730-126



Documentation

Additional Information
Technical Section
03.04.2019
pdf 2010.85 KB



CAD/CAE-Data

CAE data
WSCAD Universe 730-126



1 Compatible Products

1.1 Optional Accessories

1.1.1 Test and measurement

1.1.1.1 Testing accessories



Item No.: 210-136
Test plug; 2 mm Ø; with 500 mm cable; red

1.1.2 Tool


1.1.2.1 Operating tool

**Item No.: 210-719**


Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft

Installation Notes

Conductor termination



Press conductors into strain relief fingers.



Place upper and lower part of the socket into pre-locking position.




Press into final position using pliers.

Testing



Testing via 2.3 mm Ø test plug.

Installation



Insert plug into socket.

Marking



Marking via side marker carrier.