

## BAP-SK2020: Ball valve with handle Push 20x20



### Commercial information

Messing bolkraan met 2 steekkoppelingen. Handvat heeft een rode coating

#### Certificates

#### Applications

Potable water, Heating, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Surface protection ball	None	Diameter bolt hole	20
Material secondary spindle seal	Ethylene-propylene diene monomer rubber (EPDM)	Outer pipe diameter connection 1	20 Millimetre
With coupling connection 1	✓	Outer pipe diameter connection 2	20 Millimetre
With coupling connection 2	✓	Medium temperature (continuous)	-10 70 Degrees celsius
With drain valve	✗	Wrench width	0 Millimetre
With drain possibility (connection)	✓	Wrench width union nut	0 Millimetre
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Full bore	✗		
VdS quality mark	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Type approval according to BBR/EKS	✗		

## Related products