



BAP-SK2626: Ball valve with handle Push 26x26



Commercial information

Messing bolkraan met 2 steekkoppelingen. Handvat heeft een rode coating

Certificates

Applications

Potable water, Heating, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

| | | | |
|-------------------------------------|--|----------------------------------|------------------------|
| Surface protection ball | None | Diameter bolt hole | 26 |
| Material secondary spindle seal | Ethylene-propylene diene monomer rubber (EPDM) | Outer pipe diameter connection 1 | 26 Millimetre |
| Nominal diameter connection 1 | DN 20 | Outer pipe diameter connection 2 | 26 Millimetre |
| With coupling connection 1 | ✓ | Medium temperature (continuous) | -10 70 Degrees celsius |
| With coupling connection 2 | ✓ | Wrench width | 0 Millimetre |
| With drain valve | ✗ | Wrench width union nut | 0 Millimetre |
| With drain possibility (connection) | ✓ | | |
| With filter | ✗ | | |
| With thermometer | ✗ | | |
| Model | Straight | | |
| With insulation shell | ✗ | | |
| FM quality mark | ✗ | | |
| UL quality mark | ✗ | | |
| ULC quality mark | ✗ | | |
| LPCB quality mark | ✗ | | |
| Fire-safe | ✗ | | |
| Medically clean | ✗ | | |
| Grease-free | ✗ | | |
| Full bore | ✗ | | |
| VdS quality mark | ✗ | | |
| DVGW quality mark for gas | ✗ | | |
| DVGW quality mark for water | ✗ | | |
| KIWA certified | ✗ | | |
| Type approval according to BBR/EKS | ✗ | | |

Related products