

25-200216: Standard Ø20x2 25m



Commercial information

Henco multilayer pipe with all the **advantages** of plastic and metal

- Butt welded aluminium pipe
- 100% oxygen-tight and water vapour diffusion tight
- Low coefficient of linear expansion, similar to metal pipe
- Entirely corrosion-resistant, also resistant against chemicals and electrochemicals
- Sound-insulation similar to entirely plastic pipe
- Electron beam crosslinked inner and outer pipe
- High resistance to pressure and temperature
- Smooth surface, less loss of pressure
- Light as synthetic piping
- Flexible, easy to bend even at low temperatures, retains shape after bending

Basic unit dimensions

Height	20 mm
Length	1,000 mm
Width	20 mm
Net weight	0.148 kg

Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, Bureau Veritas, RISE, AFNOR, PZH, STF, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Underfloor Heating, Sanitary

Solutions

Building installations, Industry, Underfloor heating, Utility, Shipbuilding

Technical characteristics

Quality class inner layer	PE-Xc	Number of layers	5
Material intermediate layer	Aluminium	Outer pipe diameter	20 Millimetre
Material outer layer	Plastic (expired)	Wall thickness	2 Millimetre
Quality class outer layer	PE-Xc	Medium temperature (continuous)	- Degrees celsius 10 7 0
Glass-fibre reinforced	✘	Max. medium temperature (momentarily)	95 Degrees celsius
Diffusion-proof	✓	Max. operating pressure at 20 °C	16 Bar
Nominal diameter	DN 16	Max. operating pressure at max. medium temperature	16 Bar
System specific	✓	Wall roughness	0.00 Millimetre 7
Flexible	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Suitable for surface mounting	✓	Min. bending radius	60 Millimetre
Pipe colour	White	Min. bending radius without tools	60 Millimetre
With mantle pipe	✘	Outer diameter mantle pipe	0 Millimetre
With heating cable	✘	Thickness of thermal insulation	0 Millimetre
With thermal insulation	✘	Lambda value	0.43 Watt per metre Kelvin
SVGW certified	✘	Outer diameter thermal insulation	0 Millimetre
Capped	✘	Outer width rectangular insulation	0 Millimetre
UV resistant	✘	Outer height rectangular insulation	0 Millimetre
Halogen free	✓	Water content	0.20 Litre per metre 1
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Compliant with NF 545	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		