

Product data sheet

Item No. 96.443.5034.1

Cable assembly RST20I4KS-S 25 50SW

Connection cable, male - free end, length 5m, RST20i4, 4 pole, 250/400V, 20A, cable type H07RN-F, cross section 2,5 mm², color of coding: black



Item No.	96.443.5034.1
EAN	4015573927414
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	4
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	12.5 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

Kodierung/Keying 0 (250V/20A)

"Z"

Farbe/color

schwarz/black	.F
lichtgrau/light grey	.1
	.0

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) example (colour: black, grey)	Typ Type
96.443.XX34.1	XX in dm-Schritten	96.443.1034.1 = 10dm/L= 1000mm	RST2014KS-S 25 10SN
96.443.XX34.0		96.443.1034.0	RST2014KS-S 25 10GL
U6.443.XX34.1	XX in m-Schritten	U6.443.1234.1 = 12 m/L=12000mm	RST2014KS-S 25 X12SN
U6.443.XX34.0		U6.443.1234.0	RST2014KS-S 25 X12GL

Nennstrom/rated current 20A

Kabeltype/cable type H07RN-F4G2,5

Werkstoff/Material	2005	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
1:1				96.443.1034.0 01K	a

KONTEKT LEITUNG
 ready made cable
 Schraubenschluss ohne Drahtschutz
 screw-connection without wire protection
 Kodierung/Keying 0 (250V/20A)