



Features

• Logistics and Industry modular high bay luminaire with aisle optics to provide necessary illumination for narrow areas. Single body with 2 optical modules, 9100 lumens, 57W, 160lm/W, 4000K, CRI 80, aisle beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 410x386x133mm, Mains + control cable of 2 meter. Ball-impact-resistance according to VDE 0710-13 in suspended mounting mode.


Product Overview

Product name	Sylbay 4000K L2 9000LM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	160
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	57
Electrical protection	Class I
Control gear type	Electronic ballast


Sylbay 4000K L2 9000LM AISLE DALI
0040303

Control gear mounting	Integral
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288403038
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Sylbay 4000K L2 9000LM AISLE DALI 0040303

Product name	Sylbay 4000K L2 9000LM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Operating temperature range (°C)	-40°C...+50°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	160
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	57
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Drive current (mA)	400
Inrush Current (A)	65

Sylbay 4000K L2 9000LM AISLE DALI 0040303

Inrush Duration (µs)	268
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 20A B Breaker	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	410
Nominal Product Width (mm)	386
Weight (kg)	5.03

PACKAGING

Single packaging type	Carton
Product EAN number	5410288403038
Packaging single width (cm)	48.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288403038
Packaging outer length / height (cm)	60.0

SAFETY DATA

Optimal operating condition (°C)	-40-50
Special purpose lamp	No



Sylbay 4000K L2 9000LM AISLE DALI
0040303

Dry applications use only	No
Suitable for household illumination	No