

Features

- Surface or Suspended LED luminaire with Micro Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1447x187x56mm, White body colour, IP20, IK07, DALI Dimmable, Emergency 3 hours, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 8800lm, 73W, 120lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.


Product Overview

Product name	RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture luminous flux (lm)	8800
Luminaire efficacy (lm/W)	121
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 17
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	80
Total power consumption (W)	78
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)

RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE
0054266


Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288542669
Warranty	5 years

Photometry



RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE
0054266

Technical drawings



Data table

GENERAL DATA

Product name	RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Operating temperature range (°C)	0°C...+25°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	8800
Luminaire efficacy (lm/W)	121
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 17
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	80

RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE 0054266

Emergency duration (h)	3
------------------------	---

ELECTRICAL DATA

Total power consumption (W)	78
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C, D(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	96000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1440
Nominal Product Width (mm)	187
Weight (kg)	3.9



RANA NEO 8800LM S 1500 830 DALI EM 2L WHITE
0054266

PACKAGING

Single packaging type	Carton
Product EAN number	5410288542669
Packaging single width (cm)	6.5
Packaging single depth (cm)	21.0
DUN14 (outer)	05410288542669
Packaging outer length / height (cm)	153.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No