

**Product data sheet**

Item No. 96.452.1004.1

**Cable assembly RST20i5KS-S 15P 10SW**

 Connection cable, male - free end, length 1m, RST20i5, 5 pole, 250/400V, 16A, cable type H05VV, cross section 1,5mm<sup>2</sup>, color of coding: black


Item No.	96.452.1004.1
EAN	4015573908741
Order Unit	30 Piece(s)

**Certificates / Approvals**

**Technical data**
**General**

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

**Model**

Number of poles	5
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	1 m
--------------	-----

**Technical drawing**

Kabeltype/cable type H05VV-F5G1,5

Kodierung/keying 0  
(250V/20A)

\*Z\*

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.452.XX04.1	XX in dm-Schritten	96.452.1004.1 = 10dm x 100dm	RST201SKS-S 15P 105M
96.452.XX04.0		96.452.1004.0	RST201SKS-S 15P 106L
96.452.XX04.1	XX in m-Schritten	96.452.1204.1 = 12 m/L=1200mm	RST201SKS-S 15P X125M
96.452.XX04.0		96.452.1204.0	RST201SKS-S 15P X126L

96.452.1004.0	1	96.452.1004.0 01K
---------------	---	-------------------

**KONFEKT\_LEITUNG**

Schraubklemmen ohne Endstopfen/without screw terminals without end stop