



Features

• 2059320 BEACON XL MUSE 3K O/B DIM L3 BLK Integrated LED spotlight, black RAL 9005, unique soft-touch ring, adjustable beam angle from a 10° spot to a 70° flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 10° spot to 70° flood, optics: aspheric glass lens, colour temperature: 3000K warm white, total system power: 41W, total fixture output: 2544lm, luminaire efficacy: 62lm/W, LOR: 100%, super high colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1050mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.95, electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal en...





Product Overview

Product name	BEACON XL MUSE 3K O/B DIM L3 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
Fixture luminous flux (lm)	2544
Luminaire efficacy (lm/W)	62
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0


BEACON XL MUSE 3K O/B DIM L3 BLK
2059320

Total power consumption (W)	36
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	Black
IP rating	IP20
Product EAN number	5025768593200
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	BEACON XL MUSE 3K O/B DIM L3 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2544
Luminaire efficacy (lm/W)	62
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White

Concord

BEACON XL MUSE 3K O/B DIM L3 BLK 2059320

CRI (Ra)	97
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	36
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	900
Energy Efficiency Class (A->G) of contained light source	F

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	86000

PHYSICAL DATA

Housing colour	Black
IP rating	IP20
Nominal Product Width (mm)	165
Nominal Product Diameter (mm)	115
Weight (kg)	1.7

PACKAGING

Single packaging type	Carton
Product EAN number	5025768593200
Packaging single width (cm)	19.5
Packaging single depth (cm)	20.0

Concord

BEACON XL MUSE 3K O/B DIM L3 BLK
2059320

DUN14 (outer)	05025768593200
Packaging outer length / height (cm)	25.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No