

Product data sheet

Item No. 96.452.7003.1

Cable assembly RST20I5KSB- 15P 70GL

Connection cable, female - free end, length 7m, RST20I5, 5 pole, 250/400V, 16A, cable type H05VV, cross section 1,5mm², color of coding: black



Item No.	96.452.7003.1
EAN	4015573908697
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Female - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	7 m
--------------	-----

Technical drawing

Kabeltype/cable type H05VV-F5G1,5

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr.	L	Beispiel (Farbe: schwarz, lichtgrau)	Typ
96.452.XX03.1	XX in dm-Schritten	96.452.1003.1 = 100dm = 1000m	RST201SKSB-15P 105M
96.452.XX03.0		96.452.1003.0	RST201SKSB-15P 106L
06.452.XX03.1	XX in m-Schritten	06.452.1203.1 = 12 m/L=12000m	RST201SKSB-15P X125M
06.452.XX03.0		06.452.1203.0	RST201SKSB-15P X126L

96.452.1003.0 01K

KONFEKT_LEITUNG