

**Product data sheet**

Item No. 96.452.7034.1

**Cable assembly RST20I5KS-S 15 70SW**

 Connection cable, male - free end, length 7m, RST20i5, 5 pole, 250/400V, 16A, cable type H07RN-F, cross section 1,5mm<sup>2</sup>, color of coding: black


Item No.	96.452.7034.1
EAN	4015573909526
Order Unit	5 Piece(s)

**Certificates / Approvals**

**Technical data**
**General**

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

**Model**

Number of poles	5
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	12.2 mm
Version of cable	Male - free end

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	7 m
--------------	-----

**Technical drawing**

Kabeltype/cable type H07RN-F 5G1,5

Kodierung/keying 0  
(250V/20A)

\*Z\*

Farbe/color	.F		
schwarz/black	.1		
lichtgrau/light grey	.0		
Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ
96.452.XX34.1	XX in dm-Schritten	96.452.1034.1 = 10dm/1 = 1000mm	RST201SKS-S 15 105W
96.452.XX34.0		96.452.1034.0	RST201SKS-S 15 106L
06.452.XX34.1	XX in m-Schritten	06.452.1234.1 = 12 m/L=1200mm	RST201SKS-S 15 X125W
06.452.XX34.0		06.452.1234.0	RST201SKS-S 15 X126L

96.452.1034.0	01K
<b>KONFEKT_LEITUNG</b> <small>Schraubterminale ohne Endstopfen/terminal without screw protection caps</small>	