

Product data sheet

Item No. 96.452.8034.1

Cable assembly RST20I5KS-S 15 80SW

 Connection cable, male - free end, length 8m, RST20i5, 5 pole, 250/400V, 16A, cable type H07RN-F, cross section 1,5mm², color of coding: black


Item No.	96.452.8034.1
EAN	4015573909557
Order Unit	5 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	12.2 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	8 m
--------------	-----

Technical drawing

Kabeltype/cable type H07RN-F 5G1,5

Kodierung/keying 0
(250V/20A)

Z

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.452.XX34.1	XX in dm-Schritten	96.452.1034.1 = 10dm/L = 1000mm	RST201SKS-S 15 105W
96.452.XX34.0		96.452.1034.0	RST201SKS-S 15 106L
06.452.XX34.1	XX in m-Schritten	06.452.1234.1 = 12 m/L=1200mm	RST201SKS-S 15 X125W
06.452.XX34.0		06.452.1234.0	RST201SKS-S 15 X126L

96.452.1034.0	01K
---------------	-----

KONFEKT_LEITUNG

Schaltstromkreis ohne Erdleiter/without earth conductor with protective conductor/with PE