

SYLBATTEN IP20 L1500 SINGLE 4000K


Item No: 0045160



full range of LED Battens to replace traditional T8 battens (600mm, 1200mm, 1500mm and 1800mm), ease of installation, 18W, 2400 lum, 4000K, 25000h lifetime

Technical Assets

Dimensions (mm)




Photometrics

0.5	2.73	E(0°)	2195
		E(C0)	45
1.0	5.47	E(0°)	549
		E(C0)	11
1.5	8.20	E(0°)	244
		E(C0)	5
2.0	10.93	E(0°)	137
		E(C0)	3
2.5	13.66	E(0°)	88
		E(C0)	2
3.0	16.40	E(0°)	61
		E(C0)	1

Distance [m] Cone diameter [m] Illuminance [lx]

C0 - C180 (Half beam angle: 139.6°)



SYLBATTEN IP20 L1500 SINGLE 4000K

Item No: 0045160



General data

Product name	SYLBATTEN IP20 L1500 SINGLE 4000K
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
Warranty	2 years

Optical data

Useful luminous flux (Φuse)	2400
Fixture luminous flux (lm)	2400
Luminaire efficacy (lm/W)	133
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	18
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	120
Energy Efficiency Class (A->G) of contained light source	D, D(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	22
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	15
Max. products per 13A B Breaker	19
Max. products per 16A B Breaker	24
Max. products per 20A B Breaker	30
Connectable conductor cross section - Max (mm²)	1.5

Lifetime data

Lifespan L70 B50	25000
------------------	-------

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	43
Nominal Product Height (mm)	48
Weight (kg)	0.52

SYLBATTEN IP20 L1500 SINGLE 4000K

Item No: 0045160



Packaging

Product EAN number	5410288451602
Packaging single length / height (cm)	150.0
Packaging single width (cm)	4.25
Packaging single depth (cm)	4.72
DUN14 (inner)	15410288451609
Units per outer package	20
Packaging outer length / height (cm)	152.0
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	25.5

Safety data

Glow Wire Test (°C)	650
---------------------	-----