

Walraven Pacifyre® EFC Fire Collar

(U0425)

The flexible solution for simple to complex situations with plastic and multi-layer pipes



Features & benefits

- Simple and easy to install, without special training
- Only one box for numerous penetrations and all pipe dimensions ($\varnothing \leq 160$ mm)
- High flexibility due to close wall distance
- Suitable for difficult to access penetrations
- Zero distance between fire collars is possible
- Expansion and contraction of the pipe remains possible
- Suitable for damp conditions
- Contains no dangerous materials
- Only 3 fixing points for a fire collar of 110 mm
- The required length of the stainless steel and intumescent strip can be determined on the job site
- Only the exact amount of intumescent band is required: minimal use of material per penetration
- Left-over material can be attached to another Walraven Pacifyre® EFC fire collar
- Max. 3 pipes through 1 fire collar ($\varnothing \leq 75$ mm) when space in between is ≤ 15 mm
- Fire safe tested up to EI 120 U/U
- Tested and approved according to EN 1366-

Product Number Outside Pipe Diameter

Total Width x Total Height x Total Depth

Reference letter	D	W x H x DtT
Unit description	mm	mm x mm x mm
2132100600	16 - 175	392 x 215 x 295
2132100700	32 - 160	40 x 2 x 10,000