


Walraven WDI1 Drop-in Anchor

(L0305)

standard drop-in anchor



Features & benefits

- simple and quick installation procedure
- no collar for anchor setting at greater hole depth
- medium load capacity
- ETA ETAG001 Part 6 approval for multiple use for non-structural applications
- fire resistance class R30-R120 for design of anchorages under exposure to fire (M8-M16)
- complies with VdS CEA 4001:2024-01 (08) for applications with sprinkler systems in concrete (M8-M12)
- for loads and more information, refer to the product data sheet and/or the ETA report
- substrate type: cracked concrete, non-cracked concrete
- zinc plated



Product Number	Thread Size	Thread Type	Total Width x Total Height x Total Length	Drill Hole Diameter	Standard Embedment Depth	Minimum Substrate Thickness
Reference letter	TS	TT	W x H x L	d0	hnom	hmin
Unit description			(mm) x (mm) x (mm)	(mm)	(mm)	(mm)
6103006	M6	Metric	8 x 8 x 30	8	≥ 25	80
6103008	M8	Metric	10 x 10 x 30	10	≥ 30	80
6103010	M10	Metric	12 x 12 x 40	12	≥ 40	80
6103012	M12	Metric	15 x 15 x 50	15	≥ 50	100
6103016	M16	Metric	20 x 20 x 65	20	≥ 65	130