

## Product data sheet

Item No. 96.454.4003.1

### Cable assembly RST20I5KSB- 40P 40SW

Connection cable, female - free end, length 4m, RST20i5, 5 pole, 250/400V, 20A, cable type H05VV, cross section 4,0 mm<sup>2</sup>, color of coding: black



Item No.	96.454.4003.1
EAN	4015573920279
Order Unit	5 Piece(s)

## Certificates / Approvals



## Technical data

### General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

### Model

Number of poles	5
Nominal cross section conductor	4 mm <sup>2</sup>
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	14.3 mm
Version of cable	Female - free end

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	4 m
--------------	-----

**Technical drawing**

**Kodierung/Keying 0 (250V/20A)**

**\*X\***

**L1: braun/brown**  
**L2: schwarz/black**  
**SL: gelb/grün/yellow/green**  
**N: blau/blue**  
**L3: grau/grey**

**L1: braun/brown**  
**L2: schwarz/black**  
**SL: gelb/grün/yellow/green**  
**N: blau/blue**  
**L3: grau/grey**

all wire ends are ultrasonic welded  
 alle Adernenden ultraschallverdichtet

**Kabeltype/cable type H05VV-F5G4**

Farbe/color	.F
schwarz/black	.I
lichtgrau/light grey	.0

Teile-Nr. / part-nr.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.454.XX03.1	XX in dm-Schritten	96.454.1003.1 = 100m/1000m	RST201SKSB-L0P 105W
96.454.XX03.0		96.454.1003.0	RST201SKSB-L0P 106L
U6.454.XX03.1	XX in m-Schritten	U6.454.1203.1 = 12 m/L=1200m	RST201SKSB-L0P X125W
U6.454.XX03.0		U6.454.1203.0	RST201SKSB-L0P X126L

96.454.XX03.1	1	96.454.1003.0 01K
---------------	---	-------------------

**wieland** KONFEKT\_LEITUNG

Siehe auch: www.wieland.com