

Product data sheet

Item No. 96.454.5034.1

Cable assembly RST20I5KS-S 40 50SW

Connection cable, male - free end, length 5m, RST20i5, 5 pole,
250/400V, 20A, cable type H07RN-F, cross section 4,0 mm², color
of coding: black



Item No.	96.454.5034.1
EAN	4015573920910
Order Unit	4 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F



Cable colour	Black
Cable diameter	17 mm
Version of cable	Male - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

Kabeltype/cable type H07RN-F5G4

Kodierung/Keying 0
(250V/20A)

Z

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ
96.454.XX34.1	XX in dm-Schritten	96.454.1034.1 = 100dm = 1000m	RST201SK5-S 40 105W
96.454.XX34.0		96.454.1034.0	RST201SK5-S 40 106L
06.454.XX34.1	XX in m-Schritten	06.454.1234.1 = 12 m/L=12000m	RST201SK5-S 40 X125W
06.454.XX34.0		06.454.1234.0	RST201SK5-S 40 X126L

96.454.1034.0	01K
---------------	-----

KONFEKT_LEITUNG

Sollt sich bei einer Änderung der Zeichnung ändern. Bitte beachten Sie die Änderungen in der Zeichnung.