

Product data sheet

Item No. 96.454.8003.1

Cable assembly RST20I5KSB- 40P 80SW

Connection cable, female - free end, length 8m, RST20i5, 5 pole, 250/400V, 20A, cable type H05VV, cross section 4,0 mm², color of coding: black



Item No.	96.454.8003.1
EAN	4015573920316
Order Unit	2 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	5
Nominal cross section conductor	4 mm ²
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	14.3 mm
Version of cable	Female - free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	8 m
--------------	-----

Technical drawing

Kodierung/Keying 0 (250V/20A)

X

L1: braun/brown
L2: schwarz/black
SL: gelb/grün/yellow/green
N: blau/blue
L3: grau/grey

all wire ends are ultrasonic welded
alle Adernenden
ultraschallverdichtet

Schnittlänge/cutting length: 1-76±3%

Kabeltype/cable type H05VV-F5G4

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. / part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) / example (colour: black, grey)	Typ / type
96.454.XX03.1	XX in dm-Schritten	96.454.1003.1 = 100m/1000m	RST201SKSB-L0P 106L
96.454.XX03.0		96.454.1003.0	RST201SKSB-L0P 106L
U6.454.XX03.1	XX in m-Schritten	U6.454.1203.1 = 12 m/L=1200mm	RST201SKSB-L0P X125W
U6.454.XX03.0		U6.454.1203.0	RST201SKSB-L0P X125W

96.454.XX03.1	1	96.454.1003.0 01K
---------------	---	-------------------

wieland KONFEKT_LEITUNG

Siehe auch: www.wieland.com