

## CurveLyte

**CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK**  
**2093186**



### Product features

- CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution, with low glare filter (UGR=19). Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Warm White (3000K) LED Colour Temperature, 5000lm, 55W, 91lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



## PRODUCT OVERVIEW

Product name	CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260866
E-number SE	7505164
Warranty	5 years
Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	91
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Dimming method	DALI
Housing colour	Black
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931866

## DATA TABLE

### General data

Product name	CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001743

## CurveLyte

*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*

2093186

E-number FI	4260866
E-number SE	7505164
Warranty	5 years

### Optical data

Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	91
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 19
Photobiological Risk Group	RG0

### Electrical data

Total power consumption (W)	55
Electrical protection	Class I
Dimming method	DALI
Drive current (mA)	1200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Lifespan L70 B50	161000
Lifespan L80 B20	49000

### Physical data

Housing colour	Black
IP rating	IP20
IK rating	IK06
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	1265
Nominal Product Width (mm)	336
Nominal Product Height (mm)	46
Weight (kg)	5.8

### Packaging

Single packaging type	Carton
Product EAN number	5025768931866
Packaging single length / height (cm)	135.0
Packaging single width (cm)	41.0
Packaging single depth (cm)	16.5
DUN14 (outer)	05025768931866
Units per outer package	1
Packaging outer length / height (cm)	135.0
Packaging outer width (cm)	41.0
Packaging outer depth (cm)	16.5

## CurveLyte


*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*  
2093186

### PHOTOMETRY

0.5	1.52 1.70	E(0°) E(C90) E(C0)	4597 339 265
1.0	3.04 3.40	E(0°) E(C90) E(C0)	1024 85 67
1.5	4.57 5.09	E(0°) E(C90) E(C0)	455 38 30
2.0	6.09 6.75	E(0°) E(C90) E(C0)	256 21 17
2.5	7.61 8.45	E(0°) E(C90) E(C0)	154 14 11
3.0	9.13 10.19	E(0°) E(C90) E(C0)	114 9 7

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 119.0°)  
— C90 - C270 (Half beam angle: 113.4°)



### TECHNICAL DRAWINGS

