

START Waterproof Tubular 1500 IP66 6000lm 830 PC
0047158



Features

- START Waterproof Tubular is an aesthetically attractive integrated LED fixture. Easy to install with 304 stainless steel fixing brackets for ceiling mounting. Polycarbonate housing; 3000K; 50W; 5500lm; 110lm/W and lumen maintenance L70:B50 of 68,000 hours lifetime. IP66; IK10; Class I; 1495mm x 62mm. Can be suspended with additional accessory (SKU 0046035).


Product Overview

Product name	START Waterproof Tubular 1500 IP66 6000lm 830 PC
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate, Polyester
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4357129
Fixture luminous flux (lm)	5500
Luminaire efficacy (lm/W)	110
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP66
IK rating	IK10

START Waterproof Tubular 1500 IP66 6000lm 830 PC
0047158

Product EAN number	5410288471587
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

