


Finishing set for fourfold, potential-free push button, 24 V, with LEDs, white

Finishing set for a push button with four potential-free 24 V control buttons used to control various lighting points in one or more rooms. These control buttons are specially equipped with an LED lamp. By using the LED lamp, you know directly whether the light source is activated or not. Colour: white.



Technical data

Finishing set for fourfold, potential-free push button, 24 V, with LEDs, white.

- Function: the two keys (1 per 2 push buttons) are clicked onto the fourfold, potential-free push button at the bottom and the top and are held in place by the snap hooks on the base of the potential-free push button. The back of the two keys is equipped with two legs that push on the push buttons of the base when the key is pressed
- Number of buttons: 4
- Material finishing: polycarbonate (PC) + acrylic-styrene-acrylate (ASA)
- Type of control: push button
- Colour: white
- Colour RAL (approximately): 9010
- Colour NCS (approximately): NCS S 0502-Y50R
- Surface treatment: coloured in mass
- Text field: the central plate is placed in the centre and consists of two parts: a visible part and an attachment part. It does not have a text field
- Number of lenses: 4
- Dismantling method: pull the central plate off the mechanism
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)
 - all plastic components are halogen-free
- Dimensions of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 44.5 mm x 44.5 mm x 8.6 mm
- Marking: CE