


# START Downlight 150 IP54 1200lm 830

Item No: 0030324

**SYLVANIA**


**START**



Ceiling recessed LED downlight IP54 (from the front), perfect where limited ceiling void is available with only 45mm product depth and 150mm cutout. Ideal replacement for 1x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 12W, 3000K, Driver Current: 290mA, CRI80, 74° beam angle, Non-dimmable LED driver, IP54 from the front, IK07, (HxW) 45x165mm, Class 2, 220-240V. Meets TP(a) requirements.

## Technical Assets


### Dimensions (mm)



### Photometrics

0.5	0.81	E10° E100°	2681 382
1.0	1.61	E10° E100°	615 148
1.5	2.42	E10° E100°	273 88
2.0	3.23	E10° E100°	154 68
2.5	4.03	E10° E100°	98 53
3.0	4.84	E10° E100°	68 41

Distance [m]      Cone diameter [m]      Illuminance [lx]  
 — C0 - C180 (Half beam angle: 77.8°)



# START Downlight 150 IP54 1200lm 830

Item No: 0030324

**SYLVANIA**

## General data

Product name	START Downlight 150 IP54 1200lm 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	40
ETIM Class	EC001744
E-number FI	4278145
Warranty	5 years

## Optical data

Useful luminous flux ( $\Phi_{use}$ )	1100
Fixture luminous flux (lm)	1200
Luminous flux (lm)	1200
Luminaire efficacy (lm/W)	100
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0

## Electrical data

Total power consumption (W)	12
Current (A)	0.052
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	20
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Drive current (mA)	300
Inrush Current (A)	7.48
Inrush Duration ( $\mu$ s)	160
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	66
Max. products per 13A C Breaker	80
Max. products per 16A C Breaker	96
Max. products per 20A C Breaker	100
Max. products per 10A B Breaker	53
Max. products per 13A B Breaker	64
Max. products per 16A B Breaker	77
Max. products per 20A B Breaker	80
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# START Downlight 150 IP54 1200lm 830

Item No: 0030324

**SYLVANIA**

## Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

## Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP54/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	45
Nominal Product Diameter (mm)	165
Weight (kg)	0.286
Recessed Depth (mm)	150

## Packaging

Product EAN number	5410288303246
Packaging single length / height (cm)	19.7
Packaging single width (cm)	17.9
Packaging single depth (cm)	7.1
DUN14 (inner)	15410288303243
Units per outer package	20
Packaging outer length / height (cm)	37.9
Packaging outer width (cm)	37.6
Packaging outer depth (cm)	38.2

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-10-40