

## CurveLyte

*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*

2093186



### Product features

- CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK is a suspended LED Linear luminaire with Direct / Indirect (70/30) distribution, with low glare filter (UGR=19). Luminaire Dimensions: 1265x336x46mm, Black body colour, IP20, IK06. Constant Current, Low LED flicker (<5%), Warm White (3000K) LED Colour Temperature, 5000lm, 55W, 91lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, Lifespan 49,000 hours L80B20, Terminal block connection in the driver box. Glow Wire Test 650°C.



## PRODUCT OVERVIEW

Product name	CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK
Technology	LED
General application	Education, Hospitality, Office
ETIM Class	EC001743
E-number FI	4260866
E-number SE	7505164
Warranty	5 years
Fixture luminous flux (lm)	5000
Luminaire efficacy (lm/W)	91
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	55
Electrical protection	Class I
Dimming method	DALI
Housing colour	Black
IP rating	IP20
IK rating	IK06
Product EAN number	5025768931866

## PHOTOMETRY


## CurveLyte

*CURVELYTE 1265x330 HO LG D/I 3K DALI BLACK*  
2093186

0.5	1.52	E:0°	400'
	1.70	E:C90	65.7"
		E:C0	339
1.0	3.04	E:0°	1024
	3.40	E:C90	65.7"
		E:C0	339
1.5	4.57	E:0°	485
	5.09	E:C90	65.7"
		E:C0	339
2.0	6.09	E:0°	286
	6.75	E:C90	65.7"
		E:C0	339
2.5	7.61	E:0°	164
	8.49	E:C90	65.7"
		E:C0	339
3.0	9.13	E:0°	114
	10.19	E:C90	65.7"
		E:C0	339

Distance [m]      Core diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 113.4°)  
— C90 - C270 (Half beam angle: 113.4°)



## TECHNICAL DRAWINGS

