


VS-ENDCAP-M: End plugmale for manifold



Commercial information

Male plastic end cap for Henco manifold

Basic unit dimensions

Height	28 mm
Length	31 mm
Width	28 mm
Net weight	0.013 kg

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Max. operating pressure at 20 °C	10 Bar
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)		
System specific	✓		
Connection 1	Insert (push-fitting)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	White		
With drain valve	✗		
With de-aerator	✗		
KIWA certified	✗		
Gastec QA	✗		
Capped	✗		
With connection indicator	✗		
FM quality mark	✗		
VdS quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
Compliant with NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✗		
Gastec QA - AR 214 (H2)	✗		
Type approval according to BBR/EKS	✗		