

KubiXx 4000K 19KLM AISLE DALI
0062122




Features

- Logistics and Industry high bay luminaire with aisle optics to provide necessary illumination for narrow areas. 19700lumens, 110W, 178lm/W, 4000K, CRI80, aisle beam optic, DALI-2 dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK06.


Product Overview

Product name	KubiXx 4000K 19KLM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
Fixture luminous flux (lm)	19700
Luminaire efficacy (lm/W)	178
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	110
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	Grey
IP rating	IP65
IK rating	IK06
Product EAN number	5410288621227
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	KubiXx 4000K 19KLM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed

KubiXx 4000K 19KLM AISLE DALI 0062122

Operating temperature range (°C)	-40°C...+50°C
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	19700
Luminaire efficacy (lm/W)	178
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 22
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	110
Primary Supply/Product voltage - min (V)	220
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	800
Inrush Current (A)	65
Inrush Duration (µs)	268
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 20A B Breaker	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	95000
Lifespan L90 B10	45000

PHYSICAL DATA



KubiXx 4000K 19KLM AISLE DALI
0062122

Housing colour	Grey
IP rating	IP65
IK rating	IK06
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	330
Nominal Product Width (mm)	370
Weight (kg)	4.9

PACKAGING

Single packaging type	Carton
Product EAN number	5410288621227
Packaging single width (cm)	41.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288621227
Packaging outer length / height (cm)	48.0

SAFETY DATA

Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No