



Features

- Ambient and decorative round, recessed mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 1075lm, 10.1W, 106lm/W, 3000K, CRI 80, non-dimmable, 120,000 hours lumen maintenance (L70:B50). Drive current: 275mA, IP44, IK10, Class I, 220-240V.

Product Overview


Product name	GIOTTO 235 3000K RECESSED
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Environment	Indoor
E-number FI	4270045
Fixture luminous flux (lm)	1075
Luminaire efficacy (lm/W)	106
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	10.1
Electrical protection	Class I
Control gear type	LED driver constant current
Control gear mounting	Integrated
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White

Lumiance


GIOTTO 235 3000K RECESSED 3034751

IP rating	IP44
IK rating	IK10
Product EAN number	8711971347514
Warranty	5 years
Colour Code	830

Photometry



Technical drawings



Light your world