

Isoline DALI
ISOLINE 3380MM 4K ASYL DA 8C
0042540



Product features

- Isoline LED linear DALI dimmable luminaire for industrial and commercial applications. 3380 mm length with asymmetrical (Left) optics provide homogenous light distribution for wide, shelf areas. Suitable for DALI Dimming. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, 3 SDCM. 112 W power consumption, 16000 lm luminous flux, 143 lm/W efficacy, 3380 mm x 62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, DC 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.



PRODUCT OVERVIEW


| | |
|-----------------------------------|----------------------------------|
| Product name | ISOLINE 3380MM 4K ASYL DA 8C |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Suspended |
| Fixture rating | Enclosed |
| General application | Logistics & Industry |
| ETIM Class | EC000986 |
| Warranty | 5 years |
| Useful luminous flux (Fuse) | 16000 |
| Fixture luminous flux (lm) | 16000 |
| Luminous flux (lm) | 16000 |
| Luminaire efficacy (lm/W) | 143 |
| Correlated colour temperature (k) | 4000 |
| Colour Code | 840 |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 112 |
| Electrical protection | Class I |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI |
| Minimum dimming level (%) | 1 |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK03 |
| Product EAN number | 5410288425405 |

PHOTOMETRY

Isoline DALI

ISOLINE 3380MM 4K ASYL DA 8C

0042540



TECHNICAL DRAWINGS

