



Features

• Isoline LED linear luminaire for industrial and commercial applications. 3380 mm lenght with double asymmetrical optics provide homogenous light distribution for wide, shelf areas. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, UGR <25, 3 SDCM. 114 W power consumption, 16600 lm luminous flux, 145 lm/W efficacy, 3380 mm x62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I.Lifespan L70:B50 60,000 hours.


Product Overview

Product name	ISOLINE 3380MM 4K DASY 5C
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Fixture luminous flux (lm)	16600
Luminous flux (lm)	16500
Luminaire efficacy (lm/W)	145
Correlated colour temperature (k)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	114
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016

ISOLINE 3380MM 4K DASY 5C
0042537

IP rating	IP20
IK rating	IK03
Product EAN number	5410288425375
Warranty	5 years
Dimming method	N/A
Colour Code	840
Useful luminous flux (#use)	16600

Photometry



Technical drawings

