

Data Sheet | Item Number: 770-101

Locking lever; for flying leads; for manual operation; black

<https://www.wago.com/770-101>



Color: ■ black

Locking system WINSTA® MIDI

Implement your installation project with ease: The locking system from the WINSTA® MIDI product line is the solution for error-free electrical installation. A comprehensive range of accessories rounds out the WINSTA® product line from WAGO. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

WINSTA® MIDI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismatching from WAGO makes the electrical installation of electrical components visibly easier.

- pre-assembled versions
- fast, secure installation

Connection data

Connection 1

Actuation type	Finger-operated lever
----------------	-----------------------

Mechanical data

Suitable	for flying leads; manually operated
----------	-------------------------------------

Material data

Note (material data)

[Information on material specifications can be found here](https://www.wago.com/us/material-specifications)

Color	black
-------	-------

Insulation material	Polyamide (PA66)
---------------------	------------------

Flammability class per UL94	V0
-----------------------------	----

Fire load	0.022 MJ
-----------	----------

Weight	0.6 g
--------	-------

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332660907
Customs tariff number	85389099990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

Downloads

Environmental Product Compliance

Compliance Search



Environmental Product Compliance 770-101	↓
--	-------------------

Documentation

Bid Text

770-101	19.02.2019	xml 2.62 KB	↓
770-101	11.03.2015	doc 21.50 KB	↓

CAD/CAE-Data

CAD data	CAE data
2D/3D Models 770-101 	WSCAD Universe 770-101 
	ZUKEN Portal 770-101 