

Features

- Surface or Suspended LED Linear luminaire with Louvre + Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 616x616x50mm, Sylvania White body colour, IP20, IK07, Light Engine Dimensions: 570x130mm, Constant Current, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 2800lm, 28W, 100lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m2, Lumen Maintenance: L90B10 at 50,000 hours, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.


Product Overview

Product name	RANA LED S 600 LO 3K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
General application	Education, Hospitality, Office, Retail
ETIM Class	EC002892
E-number FI	4273506
Fixture luminous flux (lm)	2800
Luminaire efficacy (lm/W)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	28

RANA LED S 600 LO 3K LOUV+PRI W GEN2
0051454


Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP20
IK rating	IK07
Product EAN number	5410288514543
Warranty	5 years
Dimming method	N/A

Photometry



RANA LED S 600 LO 3K LOUV+PRI W GEN2
0051454

Technical drawings



Data table

GENERAL DATA

Product name	RANA LED S 600 LO 3K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
General application	Education, Hospitality, Office, Retail
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4273506
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2800
Luminaire efficacy (lm/W)	100

RANA LED S 600 LO 3K LOUV+PRI W GEN2 0051454

Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	28
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	275
Inrush Current (A)	22
Inrush Duration (µs)	250
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	28
Max. products per 13A C Breaker	36
Max. products per 16A C Breaker	45
Max. products per 20A C Breaker	56
Max. products per 10A B Breaker	17
Max. products per 13A B Breaker	22
Max. products per 16A B Breaker	27
Max. products per 20A B Breaker	34

RANA LED S 600 LO 3K LOUV+PRI W GEN2 0051454

Connectable conductor cross section - Min (mm ²)	2.5
---	-----

Connectable conductor cross section - Max (mm ²)	2.5
---	-----

LIFETIME DATA

Lifespan L70 B50	50000
------------------	-------

Lifespan L70 B10	50000
------------------	-------

Lifespan L90 B10	50000
------------------	-------

PHYSICAL DATA

Housing colour	White
----------------	-------

IP rating	IP20
-----------	------

IK rating	IK07
-----------	------

Diffuser finish	Prismatic
-----------------	-----------

Diffuser material	PC Polycarbonate
-------------------	------------------

Nominal Product Length (mm)	616
-----------------------------	-----

Nominal Product Width (mm)	616
----------------------------	-----

Nominal Product Height (mm)	50
-----------------------------	----

Weight (kg)	5.0
-------------	-----

PACKAGING

Product EAN number	5410288514543
--------------------	---------------

Packaging single length / height (cm)	67.0
---------------------------------------	------

Packaging single width (cm)	6.5
-----------------------------	-----

Packaging single depth (cm)	64.5
-----------------------------	------

DUN14 (inner)	05410288514543
---------------	----------------

Units per outer package	1
-------------------------	---

Packaging outer length / height (cm)	67.0
--------------------------------------	------

Packaging outer width (cm)	6.5
----------------------------	-----

Packaging outer depth (cm)	64.5
----------------------------	------

SAFETY DATA



RANA LED S 600 LO 3K LOUV+PRI W GEN2
0051454

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No