

TACFLEX POLYAMIDE SPIRAL CONDUITS - SPLIT TYPE



tacflex




**PLASTIC SPIRAL CONDUITS
PA 6 / SPLIT TYPE**

TECHNICAL DETAILS

| | |
|--------------------|---|
| Material | : Polyamide PA6 V2/V0 |
| Certificates | : ROHS, CE, PT, TUV, DB Din 5510 |
| Color | : Gray (RAL7031) Black (RAL9005) * Orange or any other color versions are available on request |
| Temperature range | : -40 °C + 120 °C |
| Flammability class | : UL94 V2&V0 |

Properties

- Split version
- High fatigue life
- High impact strength
- Halogen free
- Self-extinguishing
- High abrasion resistance
- High UV resistance (black)
- Full-shrink packing



PA6 YARIKLI TİP SİRİL BORU

| | |
|-------------------|---|
| Hammaddesi | : Polyamid PA6 |
| Renk | : RAL 7031 (Gri) RAL 9005 (Siyah) |
| Çalışma sıcaklığı | : -40 °C + 120 °C |
| Kullanım alanları | : Mekanik ve ekipman cihaz bağlantılarında makine, matbaa, otomotiv, lokomotif, tramvay, gemi otomatik makinaları, endüstriyel tesis montajlarında, aydınlatma ve elektrik pano montajlarında kullanılmaktadır. |

SPLIT TYPE SPA6 SPIRAL CONDUITS

| Nominal Diameter | Gray Code ■ RAL 7031 | Black Code ■ RAL 9005 | d Ø mm. | d1 Ø mm. | Roll Length mt. |
|------------------|-------------------------|--------------------------|------------|-------------|--------------------|
| 7 | OGPAY 7 | OSPAY 7 | 6,5 | 10 | 100 |
| 8,5 | OGPAY 8,5 | OSPAY 8,5 | 8,5 | 12 | 100 |
| 9 | OGPAY 9 | OSPAY 9 | 10 | 13 | 100 |
| 11 | OGPAY 11 | OSPAY 11 | 12 | 15,8 | 50 |
| 13,5 | OGPAY 13,5 | OSPAY 13,5 | 14,2 | 18,4 | 50 |
| 16 | OGPAY 16 | OSPAY 16 | 16,5 | 21,2 | 50 |
| 21 | OGPAY 21 | OSPAY 21 | 23,5 | 28,4 | 50 |
| 29 | OGPAY 29 | OSPAY 29 | 29 | 34,5 | 25 |
| 36 | OGPAY 36 | OSPAY 36 | 36 | 42,5 | 25 |
| 48 | OGPAY 48 | OSPAY 48 | 48 | 54,5 | 25 |

PRODUCT RANGE OVERVIEW

Halogen free