

Start Flood IP66 Asymmetric

Start Flood IP66 42000lm 740 ASYM
0048215



Product features


- Exterior LED Floodlight, comes complete with 1500mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 4000K, Non-dimming, 41000lm, 300W, 137lm/W, CRI70, Asymmetrical Wide beam angle (65° x 120° imax@55°), 100000 hrs L90B10 lifespan, 567 x 465 x 97mm (LxWxD) dimensions, 9.6kg weight.



PRODUCT OVERVIEW

Product name	Start Flood IP66 42000lm 740 ASYM
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579467
Warranty	5 years
Useful luminous flux (Fuse)	41000
Fixture luminous flux (lm)	41000
Luminaire efficacy (lm/W)	137
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	70
Beam Angle (°)	65*120
Photobiological Risk Group	RG1
Total power consumption (W)	300
Electrical protection	Class I
IP rating	IP66
IK rating	IK08
Product EAN number	5410288482156

PHOTOMETRY



Start Flood IP66 Asymmetric *Start Flood IP66 42000lm 740 ASYM* 0048215

TECHNICAL DRAWINGS

