




Features

• Logistics and Industry modular high bay luminaire with wide optics to provide homogenous light distribution for open space areas. Twin body with 6 optical modules, 47400 lumens, 327W, 145lm/W, 4000K, CRI 80, wide beam optic. Fitted with a high bay PIR for 360° detection up to 16m range at 15m mounting height. 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08 (sensor IK03), (LxWxH) 726x386x133mm, Mains + control cable of 2 meter.




Product Overview

Product name	Sylbay 4000K L6 47000LM WIDE PIR
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Fixture luminous flux (lm)	47400
Luminaire efficacy (lm/W)	145
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG1
Total power consumption (W)	327
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Housing colour	Grey


Sylbay 4000K L6 47000LM WIDE PIR
0040332

IP rating	IP65
IK rating	IK08
Product EAN number	5410288403328
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Sylbay 4000K L6 47000LM WIDE PIR
Technology	LED

Sylbay 4000K L6 47000LM WIDE PIR 0040332

Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
Operating temperature range (°C)	-20°C...+35°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	47400
Luminaire efficacy (lm/W)	145
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 23
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	327
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.96
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Drive current (mA)	750
Inrush Current (A)	4.65
Inrush Duration (µs)	584
Glow Wire Test (°C)	650

Sylbay 4000K L6 47000LM WIDE PIR 0040332

Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	833
Nominal Product Width (mm)	386
Weight (kg)	8.07

PACKAGING

Single packaging type	Carton
Product EAN number	5410288403328
Packaging single width (cm)	47.5
Packaging single depth (cm)	27.0
DUN14 (outer)	05410288403328
Packaging outer length / height (cm)	92.0

SAFETY DATA

Optimal operating condition (°C)	-20-35
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No