

Features

• Isoline LED linear luminaire for industrial and commercial applications. 3380mm length with 1.7m blank section, with asymmetrical (Right) optics provide homogenous light distribution for aisles and focus areas. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, 3 SDCM. 57W power consumption, 8000lm luminous flux, 140 lm/W efficacy, 3380 mm x62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.


Product Overview

Product name	ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC000986
Fixture luminous flux (lm)	8000
Luminous flux (lm)	8000
Luminaire efficacy (lm/W)	140
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	57
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016

ISOLINE 3380MM 4K 1.7ASYR 1.7BLK
0042562

IP rating	IP20
IK rating	IK03
Product EAN number	5410288425627
Warranty	5 years
Dimming method	N/A
Colour Code	840
Useful luminous flux (#use)	8000

Photometry



Technical drawings

