



Data Sheet | Item Number: 734-173/108-000

THT male header; 1.0 x 1.0 mm solder pin; angled; 100% protected against mismatching; Threaded flange; Pin spacing 3.5 mm; 13-pole; light gray

<https://www.wago.com/734-173/108-000>




Color: ■ light gray



Dimensions in mm

$L = (\text{pole no.} \times \text{pin spacing}) + 9.5 \text{ mm}$
 $L1 = (\text{pole no.} \times \text{pin spacing}) + 4.9 \text{ mm}$



Male connector, 734 Series, solder pin dimensions 1 x 1 mm

Seamless electrical installations are guaranteed with this male connector (item number 734-173/108-000). Dimensions: (55 x 12.3 x 10.3) mm (width x height x depth).

The contact surface is coated with tin. The pcb connector is designed for THT soldering.



Notes	
Safety Information	The MCS – MULTI CONNECTION SYSTEM includes connectors without breaking capacity in accordance with DIN EN 61984. When used as intended, these connectors must not be connected/disconnected when live or under load. When used as intended, these connectors must not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.
Variants:	Other pole numbers Gold-plated or partially gold-plated contact surfaces Other versions (or variants) can be requested from WAGO Sales or configured at https://configurator.wago.com/ .

Electrical data			
Ratings per		IEC/EN 60664-1	
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	160 V	160 V	320 V
Rated impulse withstand voltage	2.5 kV	2.5 kV	2.5 kV
Rated current	10 A	10 A	10 A
Approvals per		UL 1059	
Use group		B	C D
Rated voltage		300 V	- 300 V
Rated current		10 A	- 10 A

Approvals per		CSA	
Use group	B	C	D
Rated voltage	300 V	-	300 V
Rated current	10 A	-	10 A

Connection Data	
Total number of potentials	13
Number of connection types	1
Number of levels	1

Connection 1	
Pole number	13

Physical data	
Pin spacing	3.5 mm / 0.138 inches
Width	55 mm / 2.165 inches
Height	12.3 mm / 0.484 inches
Height from the surface	8.5 mm / 0.335 inches
Depth	10.3 mm / 0.406 inches
Solder pin length	3.8 mm
Solder pin dimensions	1 x 1 mm
Drilled hole diameter with tolerance	1.4 (+0.1) mm

Mechanical data	
Variable coding	Yes
Anti-rotation protection	Yes



Plug-in connection		
Contact type (pluggable connector)		Male connector/plug
Connector (connection type)		for PCB
Mismating protection		Yes
Mating direction to the PCB		0°
Locking of plug-in connection		Threaded flange

PCB contact		
PCB contact		THT
Solder pin arrangement		over the entire male connector (in-line)
Number of solder pins per potential		1

Material data		
Note (material data)		Information on material specifications can be found here
Color		light gray
Material group		I
Insulation material (main housing)		Polyamide (PA66)
Flammability class per UL94		V0
Contact material		Electrolytic copper (E _{Cu})
Contact Plating		Tin
Fire load		0.058 MJ
Weight		4 g

Environmental requirements		
Limit temperature range		-60 ... +100 °C
Processing temperature		-35 ... +60 °C

Commercial data		
Product Group		3 (Multi Conn. System)
PU (SPU)		100 pcs
Packaging type		Box
Country of origin		PL
GTIN		4045454759148
Customs tariff number		85366930000

Product Classification		
UNSPSC		39121409
eCl@ss 10.0		27-44-04-02
eCl@ss 9.0		27-44-04-02
ETIM 9.0		EC002637
ETIM 10.0		EC002637
ECCN		NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	61a460e3-32c1-409e-bd88-423da1ea2fc6
SCIP notification number (Belgium)	5097369a-b7e3-44d7-9e44-1b1a671e697a
SCIP notification number (Bulgaria)	943f747f-2a3a-4061-8006-6f7947f4d77a
SCIP notification number (Czech Republic)	3934dcc6-07fc-4850-bc1f-9aee37851afb
SCIP notification number (Denmark)	4042ea3b-a2c7-4ca7-88fb-43368fc75c3d
SCIP notification number (Finland)	95fe16e5-630e-4a95-89ab-e04f90ef4276
SCIP notification number (France)	2471b351-5ddb-481d-8fe3-9d5e6effbb66c
SCIP notification number (Germany)	ab5e97b3-2071-4d09-96b3-cce1ceae90fb
SCIP notification number (Hungary)	8614ed72-b571-409a-9e3b-2ccba9a55565
SCIP notification number (Italy)	811dc429-bbe6-4889-9ed4-d020abec61be
SCIP notification number (Netherlands)	42467faa-9d59-400d-90e3-c07062e8200b
SCIP notification number (Poland)	2d4d2e7a-c8af-45b0-8a11-2e9a05c5d2a0
SCIP notification number (Romania)	ee074979-8e73-4499-8e64-c8045a2b8cad
SCIP notification number (Sweden)	89aac51b-5174-4679-ab1e-8768ea12bc80

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
734-173/108-000

↓

Documentation

Additional Information

Technical Section

03.04.2019

pdf
2027.26 KB

↓

CAD/CAE-Data

CAD data

2D/3D Models
734-173/108-000

↓

CAE data

ZUKEN Portal
734-173/108-000

↓

PCB Design

Symbol and Footprint
via SamacSys
734-173/108-000

↓

Symbol and Footprint
via Ultra Librarian
734-173/108-000

↓

1 Compatible Products

1.1 System counterpart

1.1.1 Female connector/socket



Item No.: 734-113/107-000
1-conductor female connector; CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 13-pole; 100% protected against mismatching; Screw flange; 1,50 mm²; light gray



Item No.: 2734-113/107-000
1-conductor female connector; push-button; Push-in CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 13-pole; 100% protected against mismatching; Screw flange; 1,50 mm²; light gray

1.2 Optional Accessories

1.2.1 Coding

1.2.1.1 Coding




Item No.: 734-159
Coding key; to be snapped above top level; black



Item No.: 734-130
Coding key; to be snapped above top level; white

Installation Notes

Coding



Coding a male header – fitting coding key(s).