

## Product data sheet

Item No. G3.032.0502.2

### Cable assembly GST18i3K1BS 15G 50WS

geis® Extension cable female - male; length: 5m; type GST18i3;  
3-pole; 250 V / 20 A; colour of coding: white with white strain-relief;  
cable: H07RN-F 3G2,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | G3.032.0502.2 |
| EAN        | 4015573720749 |
| Order Unit | 10 Piece(s)   |

## Certificates / Approvals

### Technical data

#### General

|                                          |        |
|------------------------------------------|--------|
| Rated current                            | 16 A   |
| Rated voltage                            | 250 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | White  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | White  |

#### Model

|                                 |                  |
|---------------------------------|------------------|
| Number of poles                 | 3                |
| Nominal cross section conductor | 1.5 mm²          |
| Degree of protection (IP)       | IP40             |
| Cable type                      | H07RN-F          |
| Cable colour                    | Black            |
| Cable diameter                  | 9.8 mm           |
| Version of cable                | Female - male    |
| Type of cord set                | Connecting cable |
| Version cable end 1             | GST18i3 socket   |

|                     |              |
|---------------------|--------------|
| Version cable end 2 | GST18i3 plug |
|---------------------|--------------|

**Material**

|                                              |            |
|----------------------------------------------|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | No         |
| Continuous temperature of cable              | 60 °C      |
| Insulation components continuous temperature | 100 °C     |

**Dimensions**

|              |     |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|