



Walraven RapidStrut® Cross Connector G2 (BUP1000)

(H28134)

to make Strut rail fabrications



Features & benefits

- connector with pre-assembled Walraven RapidStrut® Slide nut(s)
- to make fabrication with Walraven RapidStrut® Rail
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- 'Direct Twist' technology for easy and secure installation
- visual guide to check the position of the slide nut
- optimized for easy installation with electrical tools
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227



Product Number	Angle	Total Width x Total Height x Total Length	Material Thickness	Width	Torque Moment For Installation
Reference letter	<i>a</i>	<i>W x H x L</i>	<i>MT</i>	<i>w</i>	<i>T inst.</i>
Unit description	(DEG)	(mm) x (mm) x (mm)	(mm)	(mm)	(Nm)
665885402	90	40 x 34.75 x 132	4	40	40
665885404	90	40 x 54.75 x 132	4	40	40
665885405	90	40 x 64.75 x 132	4	40	40
665885406	90	40 x 74.75 x 132	4	40	40
665885408	90	40 x 94.75 x 132	4	40	40