


WMB marking card; as card; MARKED; 11 ... 20 (10x); stretchable 5 - 5.2 mm; Horizontal marking; snap-on type; green



Similar to illustration

Marking method	Thermal transfer
Marking	11 ... 20
Marking (number)	10
Marking direction	Horizontal marking
Marking color	black
Marking type	Numbers
Marking differentiation	Consecutive numbers per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V2

Marker/strip width	5 ... 5.2 mm
Marker width	5 mm

Smear resistance	EN 60998-1:2004
------------------	-----------------

Color	green
UV resistance	EN 60068-2-5:2010 Procedure B
Halogen-free	Yes
Weight	8.8 g
Fire load	0.264 MJ



Commercial data	
eCl@ss 10.0	27-14-11-37
eCl@ss 9.0	27-14-11-37
ETIM 8.0	EC000761
ETIM 7.0	EC000761
PU (SPU)	50 (5) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454634261
Customs tariff number	4911990000

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption


Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 793-5503/000-023	

CAD/CAE-Data	
CAE data	
EPLAN Data Portal 793-5503/000-023	

Installation Notes

Application



Separating a strip from the WMB or WMB marker card.



Stretching a WMB marker strip.



Separating an individual marker from the WMB marker strip – for larger terminal blocks.



Snapping a marking strip into the marker slot.

Marking	
	Snapping a WMB marker strip into the marker slot of the double marker carrier.
	Snapping a marking strip into the marker slot.

