




Color: ■ blue Similar to illustration

Technical data	
Marking method	Thermal transfer
Marking	101 ... 150
Marking (number)	2
Marking direction	Horizontal marking
Marking color	black
Marking type	Numbers
Marking differentiation	Consecutive numbers per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V2

Physical data	
Marker/strip width	5 ... 5.2 mm
Marker width	5 mm

Mechanical data	
Smear resistance	EN 60998-1:2004

Material data	
Color	blue
UV resistance	EN 60068-2-5:2010 Procedure B
Halogen-free	Yes
Weight	8.8 g
Fire load	0.264 MJ



Commercial data	
eCl@ss 10.0	27-14-11-37
eCl@ss 9.0	27-14-11-37
ETIM 8.0	EC000761
ETIM 7.0	EC000761
PU (SPU)	50 (5) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454508111
Customs tariff number	4911990000

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 793-5508/000-006	

CAD/CAE-Data	
CAE data	
EPLAN Data Portal 793-5508/000-006	

Installation Notes

Application			
Separating a strip from the WMB or WMB marker card.	Stretching a WMB marker strip.	Separating an individual marker from the WMB marker strip – for larger terminal blocks.	Snapping a marking strip into the marker slot.

Marking	
Snapping a WMB marker strip into the marker slot of the double marker carrier.	Snapping a marking strip into the marker slot.

