



Features

- Logistics and Industry high bay luminaire with aisle optics to provide necessary illumination for narrow areas. 32500lumens, 188W, 172lm/W, 4000K, CRI80, aisle beam optic, SylSmart SSA dimmable without PIR motion detection, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK06.

Product Overview


Product name	KUBIXX 4000K 32KLM AISLE SSA N
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture rating	Enclosed
Fixture luminous flux (lm)	32500
Luminaire efficacy (lm/W)	172
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 23
Photobiological Risk Group	RG1
Total power consumption (W)	188
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	Grey
IP rating	IP65
IK rating	IK06
Product EAN number	5410288621685

KUBIXX 4000K 32KLM AISLE SSA N
0062168


Warranty

5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	KUBIXX 4000K 32KLM AISLE SSA N
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Suspended



KUBIXX 4000K 32KLM AISLE SSA N
0062168

Fixture rating	Enclosed
Operating temperature range (°C)	-40°C...+50°C
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	32500
Luminaire efficacy (lm/W)	172
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 23
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	188
Primary Supply/Product voltage - min (V)	220.0
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	920
Inrush Current (A)	85
Inrush Duration (µs)	215
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 20A B Breaker	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	95000
Lifespan L90 B10	45000



KUBIXX 4000K 32KLM AISLE SSA N
0062168

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK06
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	732
Nominal Product Width (mm)	280
Weight (kg)	6.7

PACKAGING

Single packaging type	Carton
Product EAN number	5410288621685
Packaging single width (cm)	32.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288621685
Packaging outer length / height (cm)	48.0

SAFETY DATA

Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No